



COM SISTEMA SPEEDY (CLICK-CLACK) (a)

φA int.	φB	C	D	ESP. INOX #A.	ESP. INOX #B.
80.4	130.4	325	88	0.4	0.4
100.4	150.4	325	88	0.4	0.4
125.4	175.4	325	88	0.4	0.4
130.4	180.4	325	88	0.4	0.4
150.4	200.4	335	88	0.4	0.4

COM SISTEMA SPEEDY (CLICK-CLACK) (a)

φA int.	φB	C	D	ESP. INOX #A.	ESP. INOX #B.
180.4	230.5	380	88	0.4	0.5
200.4	250.5	400	88	0.4	0.5
250.5	300.5	450	88	0.5	0.5
300.5	350.5	500	88	0.5	0.5
350.5	400.5	550	88	0.5	0.5

TIPOS DE INOX DISPONIVEL					
LA	LA DE ROCHA 702K2-ROXUL®1000				
METAL	(a) ACO INOXIDAVEL 0.4mm 304		METAL	(b) ACO INOXIDAVEL 0.5mm 304	
METAL	(a) ACO INOXIDAVEL 0.4mm 316		METAL	(b) ACO INOXIDAVEL 0.5mm 316	
DESENHOU	DATA	NOME	RUBRICA	APARTADO 8 3781-901 AVELAS DE CAMINHO PORTUGAL	
PRELECTOU	20.05.2014	J. C. CASTANHEIRA	<i>J. C. Castanheira</i>	Tel.: +351 234 730 800	
VERIFICOU	20.05.2014	J. C. CASTANHEIRA		Fax.: +351 234 730 801	
ESCALA	DESIGNAÇÃO:			www.inarel.pt	
FIT	T 90° INOX PAREDE DUPLA			d@ecrica@inarel.pt	
TOLER.				Desenho Nº DUP.000009	